

AC/DC Hour Meter Round

Panel Mount
Series N530

Model Code N530 0200 8111 0000



IMD Europe GmbH · Auf dem Molzberg 2 · D-57548 Kirchen

Quality Features



Absolut dust-, fresh-, & saltwater resistant till 20m underwatersurface.



Due to a self-contained battery it has a life cycle of 12 years.



Extrem shock proof up to at least 45G



High contrast LCD display is always lit and is polarized to prevent discoloration from UV exposure.



Pressure washer cleaning possible.



No polarity = easy to install

Product Pictures



Top View



Perspective View



Cutout Diameter



imperial (metric)

OEM and Packaging

Bubble Wrap Bag

- Hour Meter
- Includes fix clip



Apply for

For any device with key-switch start and electrical hookup.

5- 277 VDC or AC 50/60 Hz

For three-phase-devices where the plus terminal has to be linked to one face and the minus terminal has to be linked to neutral.

This digital meter can be installed where was an analog meter before.



Integrated Functions


for N530 0200 8111 0000

Hours only

No Timer

No Service Alerts


Installation Instruction



In-line hookup:

- Input 5-277V AC/DC
- non-polarized
- Input impedance: 2m

Accessory



Gasket

Although our products are certified water resistant there are other non-waterproof products integrated in the equipment. GDI-Gaskets are the perfect solution for protecting other gadgets from getting wet.